

SAFETY DATA SHEET



Date Issued : 07/21/2000
 MSDS No : 210180
 Date-Revised : 11/17/2017
 Revision No : 16

Mineral Spirits

1. PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: Mineral Spirits
PRODUCT DESCRIPTION: Mineral Spirits
PRODUCT CODE: 210180
PRODUCT FORMULATION NAME: Mineral Spirits
CHEMICAL FAMILY: Petroleum Hydrocarbons
MOLECULAR FORMULA: Mixture
GENERIC NAME: Stoddard Solvent, NAPHTHA SOLVENT
ACTIVE INGREDIENT(S): Stoddard solvent; Ethyl Benzene; 1,2,4-Trimethylbenzene

DISTRIBUTOR

AMERICHEM SALES COMPANY LLC
 340 NORTH ST.
 MASON, MI 48854
Emergency Phone: 517-676-9363

24 HR. EMERGENCY TELEPHONE NUMBERS

CHEMTREC (U.S.): (800) 424-9300
CANUTEC (613) 996-6666

COMMENTS: To the best of our knowledge, this Safety Data Sheet conforms to the requirements of US OSHA 29 CFR 1910.1200, 91/155/EEC and Canadian Hazardous Products Act.

2. HAZARDS IDENTIFICATION

GHS CLASSIFICATIONS

Health:

Aspiration Hazard, Category 1
 Skin Irritation, Category 2
 Eye Irritation, Category 2B
 Target Organ Toxicity (Single exposure), Category 3

Physical:

Flammable Liquids, Category 3

GHS LABEL



Flammable
Liquid



Exclamation
mark



Health
hazard

SIGNAL WORD: WARNING

HAZARD STATEMENTS

H226: Flammable liquid and vapour.
 H320: Causes eye irritation.
 H316: Causes mild skin irritation.
 H315: Causes skin irritation.
 H332: Harmful if inhaled.
 H302: Harmful if swallowed.
 H242: Heating may cause a fire.
 H335: May cause respiratory irritation.
 H304: May be fatal if swallowed and enters airways.

SAFETY DATA SHEET



Date Issued : 07/21/2000
 MSDS No : 210180
 Date-Revised : 11/17/2017
 Revision No : 16

Mineral Spirits

Precautionary statement(s)

Prevention:

- P260: Do not breathe dust/fume/gas/mist/vapours/spray.
- P271: Use only outdoors or in a well-ventilated area.
- P202: Do not handle until all safety precautions have been read and understood.
- P240: Ground and bond container and receiving equipment.
- P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P243: Take action to prevent static discharges.
- P241: Use explosion-proof [electrical/ventilating/lighting/...] equipment.
- P242: Use non-sparking tools.
- P281: Use personal protective equipment as required.
- P264: Wash ... thoroughly after handling.
- P280: Wear protective gloves/protective clothing/eye protection/face protection.

Response:

- P312: Call a POISON CENTER/doctor/...if you feel unwell.
- P331: Do NOT induce vomiting.
- P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.
- P303+P361+P353: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
- P301+P310: IF SWALLOWED: Immediately call a POISON CENTER/doctor/...
- P307+P311: IF exposed: Call a POISON CENTER or doctor/physician.
- P337+P313: If eye irritation persists: Get medical advice/attention.
- P332+P313: If skin irritation occurs: Get medical advice/attention.

Storage:

- P405: Store locked up.
- P403: Store in a well-ventilated place.
- P403+P233: Store in a well-ventilated place. Keep container tightly closed.
- P403+P235: Store in a well-ventilated place. Keep cool.

EMERGENCY OVERVIEW

PHYSICAL APPEARANCE: Clear, Colorless liquid.

IMMEDIATE CONCERNS: CAUTION! May cause eye and skin irritation.

POTENTIAL HEALTH EFFECTS

EYES: Moderate Irritation and Discomfort.

SKIN: Moderate irritation and discomfort possible. Defatting of skin, redness and chemical dermatitis possible. Toxic systemic effects from absorption are possible.

INGESTION: Gastrointestinal tract irritation and/or discomfort is possible.

INHALATION: Moderate respiratory discomfort and/or headaches. Toxic systemic effects from inhalation are expected to be minor.

ROUTES OF ENTRY: Absorption, Inhalation, Ingestion

TARGET ORGAN STATEMENT: Skin, Mucous membranes and Lungs.

CANCER STATEMENT: Contains material that may cause cancer. Risk of cancer depends on duration and level of exposure. Inadequate evidence available to evaluate the cancer hazard of this material.

3. COMPOSITION / INFORMATION ON INGREDIENTS

SAFETY DATA SHEET



Date Issued : 07/21/2000
 MSDS No : 210180
 Date-Revised : 11/17/2017
 Revision No : 16

Mineral Spirits

Chemical Name	Wt.%	CAS
Stoddard solvent	100	8052-41-3
Ethyl Benzene	0.1	100-41-4
1,2,4-Trimethylbenzene	0.5 - 5	95-63-6

4. FIRST AID MEASURES

EYES: Immediately flush eyes with plenty of water for 15 minutes. If irritation persists, seek medical attention.

SKIN: Remove contaminated clothing, wash contaminated area thoroughly with soap and water. If redness or irritation occurs, seek medical attention.

INGESTION: Do not induce vomiting due to aspiration hazard. If vomiting occurs lower head below knees to avoid aspiration. Seek immediate medical attention.

INHALATION: Remove victim from area of exposure. If unconscious, give oxygen. Give artificial respiration if not breathing. Get immediate medical attention.

SIGNS AND SYMPTOMS OF OVEREXPOSURE

CHRONIC EFFECTS: Chronic effects of ingestion and subsequent aspiration into the lungs may cause pneumatocele (lung tumor) formation and chronic lung dysfunction.

5. FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA: Use dry chemical, foam, or carbon dioxide.

HAZARDOUS COMBUSTION PRODUCTS: Oxides of carbon and noxious fumes.

EXPLOSION HAZARDS: Vapor accumulations may flash and/or explode if ignited. Keep ignition sources, open flames, ect., away from these fumes.

FIRE FIGHTING PROCEDURES: Proper respiratory equipment to protect against the hazardous effects of combustion products is recommended. Water in a straight hose stream may cause fire to spread and should be used as a cooling medium only.

6. ACCIDENTAL RELEASE MEASURES

SMALL SPILL: Extinguish possible sources of ignition. Evacuate all unprotected personnel and ventilate area. Only personnel equipped with proper respiratory, skin/eye protection should enter spill area. Dike area to contain spill and clean up by absorbing on an inert absorbant or other means. Don't flush into sewers or natural waterways.

LARGE SPILL: Contain material as described above and call the local fire or police department for immediate emergency assistance.

7. HANDLING AND STORAGE

HANDLING: Store in a cool, dry, ventilated area away from excessive heat, sparks and open flames. Avoid prolonged or repeated contact with skin and/or breathing of vapors when handling. Keep containers closed when not in use.

STORAGE: Store unopened containers under cool, dry and ventilated conditions. Keep away from heat, sparks and flame.

STORAGE TEMPERATURE: Ambient

LOADING TEMPERATURE: AMBIENT

SHELF LIFE: THE SHELF LIFE OF THIS PRODUCT IS UNDETERMINED, BUT MAY BECOME SUSPECT ONE YEAR FROM THE DATE OF PURCHASE.

ELECTROSTATIC ACCUMULATION HAZARD: Static Hazard: Electrostatic charge may accumulate and create a hazardous condition when handling this material. To minimize this hazard, bonding and grounding may be necessary but may not, by

SAFETY DATA SHEET



Date Issued : 07/21/2000
 MSDS No : 210180
 Date-Revised : 11/17/2017
 Revision No : 16

Mineral Spirits

themselves, be sufficient. Review all operations, which have the potential of generating an accumulation of electrostatic charge and /or a flammable atmosphere(including tank and container filling, splash filling, tank cleaning, sampling, gauging,switch loading, filtering, mixing, agitation, and vacuum truck operations) and use appropriate mitigating proceduers. For more information, refer to OSHA Standard 29 CFR 1910.106, Flammableand Combustible Liquids, NFPA 77, Recomend Practice on Static Electricity' (liquids, powders, and dust), and/or the American Petroleum Institute (API) Recommended Practice 2003, Protection Against Ignitions Arising Out of Static, Lightning, and Stray Currents.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE GUIDELINES

OSHA HAZARDOUS COMPONENTS (29 CFR1910.1200)				
EXPOSURE LIMITS				
Chemical Name	Type		ppm	mg/m ³
Stoddard solvent	OSHA PEL	TWA	500 ppm	2900 mg/m ³
		STEL	ppm	mg/m ³
	ACGIH TLV	TWA	100 ppm	572 mg/m ³
		STEL	ppm	mg/m ³
	Supplier OEL	TWA	NL	NL
		STEL	NL	NL
Ethyl Benzene	OSHA PEL	TWA	100	435
	ACGIH TLV	TWA	20 ppm	
		STEL	ppm	
1,2,4-Trimethylbenzene	OSHA PEL	TWA	ppm	
	ACGIH TLV	TWA	25 ppm	123

ENGINEERING CONTROLS: If current ventilation practices are not adequate to maintain airborne concentrations below the established exposure guidelines, additional ventilation or exhaust systems may be required. Where explosive mixtures may be present, electrical systems safe for such locations must be used.

PERSONAL PROTECTIVE EQUIPMENT

EYES AND FACE: Wear safety glasses with side shields or goggles when handling this material.

SKIN: To prevent any contact, wear impervious protective clothing such as nitrile or butyl rubber gloves, apron, boots or whole bodysuit, as appropriate.

RESPIRATORY: Use NIOSH/MSHA approved respirators when vapors or mist concentrations exceed permissible exposure limits.

PROTECTIVE CLOTHING: Chemical resistant boots, apron, etc. as necessary to prevent contamination of clothing and skin contact.

WORK HYGIENIC PRACTICES: Good personal hygiene practices should always be followed.

9. PHYSICAL AND CHEMICAL PROPERTIES

SAFETY DATA SHEET



Date Issued : 07/21/2000
 MSDS No : 210180
 Date-Revised : 11/17/2017
 Revision No : 16

Mineral Spirits

Chemical Name	Flash Point (°C)	Specific Gravity
Stoddard solvent	43	0.79

PHYSICAL STATE: Liquid

ODOR: Mild Hydrocarbon Odor

APPEARANCE: Clear

COLOR: Colorless

pH: Not Applicable

PERCENT VOLATILE: 100

FLASHPOINT AND METHOD: (105°F) to (110°F) ASTM D56

FLAMMABLE LIMITS: 0.5 to 6.0

AUTOIGNITION TEMPERATURE: (446°F)

VAPOR PRESSURE: 2.1 mmHg at (68°F)

VAPOR DENSITY: 4.7 (Air=1)

BOILING POINT: (300°F) to (400°F) ASTM D-2887

FREEZING POINT: (-85°F) to (-13°F)

SOLUBILITY IN WATER: Negligible

EVAPORATION RATE: Not Available

SPECIFIC GRAVITY: 0.78 to 0.79 (water=1)

10. STABILITY AND REACTIVITY

REACTIVITY: No

HAZARDOUS POLYMERIZATION: Will not occur

STABILITY: Stable

CONDITIONS TO AVOID: Exposure to excessive heat, open flames and sparks. Avoid conditions that favor the formation of excessive mists and/or fumes.

HAZARDOUS DECOMPOSITION PRODUCTS: Oxides of Carbon when burned.

INCOMPATIBLE MATERIALS: Strong oxidizing agents.

11. TOXICOLOGICAL INFORMATION

ACUTE TOXICITY

DERMAL LD₅₀: > 2000 mg/kg (rabbit)

ORAL LD₅₀: > 7000 mg/kg (rat)

INHALATION LC₅₀: 21 mg/l for 1 hr (calculated)

CARCINOGENICITY

Chemical Name	IARC Status
Ethyl Benzene	2B

12. ECOLOGICAL INFORMATION

ENVIRONMENTAL DATA: This naphtha is potentially toxic to freshwater and saltwater ecosystems. It will normally float on water

SAFETY DATA SHEET



Date Issued : 07/21/2000
 MSDS No : 210180
 Date-Revised : 11/17/2017
 Revision No : 16

Mineral Spirits

with its lighter components evaporation rapidly.

ECOTOXICOLOGICAL INFORMATION: Ecological effects testing has not been conducted on this material. If spilled, this naphtha, its storage tank water bottoms and sludge, and any contaminated soil or water may be hazardous to human, animal, and aquatic life. If released from its container, this material will probably contribute to the creation of atmospheric smog. n-Heptane, heptane isomers, and octane isomers all have estimated half-lives, of between 2.4 and 4.4 days in air when photochemical hydroxyl and/or nitrate radicals are present.

13. DISPOSAL CONSIDERATIONS

DISPOSAL METHOD: Conditions of use may cause this material to become a hazardous waste as defined by state or federal law. Use approved treatment, transporters and disposal sites.

FOR LARGE SPILLS: Extinguish possible sources of ignition. Evacuate all unprotected personnel and ventilate area. Only personnel equipped with proper respiratory, skin/eye protection should enter spill area. Dike area to contain spill and clean up by absorbing on an inert absorbent or other means. Don't flush into sewers or natural waterways.

PRODUCT DISPOSAL: Dispose of at a supervised incineration facility or an appropriate waste disposal facility according to current applicable laws and regulations and product characteristics at time of disposal.

EMPTY CONTAINER: Vapor accumulations may flash and/or explode if ignited. Keep ignition sources, open flames, etc. away from these fumes.

14. TRANSPORT INFORMATION

DOT (DEPARTMENT OF TRANSPORTATION)

PROPER SHIPPING NAME: Petroleum Distillates, N.O.S.

PRIMARY HAZARD CLASS/DIVISION: 3

UN/NA NUMBER: 1268

PACKING GROUP: III

LABEL: Class 3, Flammable Liquid

AIR (ICAO/IATA)

SHIPPING NAME: Petroleum Distillates, N.O.S.

UN/NA NUMBER: 1268

PRIMARY HAZARD CLASS/DIVISION: 3

PACKING GROUP: III

VESSEL (IMO/IMDG)

SHIPPING NAME: Petroleum Distillates, N.O.S.

UN/NA NUMBER: 1268

PRIMARY HAZARD CLASS/DIVISION: 3

PACKING GROUP: III

15. REGULATORY INFORMATION

UNITED STATES

SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT)

311/312 HAZARD CATEGORIES: Fire Hazard, Acute (Immediate) Health Hazard.

313 REPORTABLE INGREDIENTS: 1,2,4-Trimethylbenzene (Pseudocumene) [CAS No. 95-63-6] conc.: 1 to 4%

SAFETY DATA SHEET



Date Issued : 07/21/2000
 MSDS No : 210180
 Date-Revised : 11/17/2017
 Revision No : 16

Mineral Spirits

EPCRA SECTION 313 SUPPLIER NOTIFICATION

Chemical Name	Wt.%	CAS
1,2,4-Trimethylbenzene	0.5 - 5	95-63-6

CERCLA (COMPREHENSIVE RESPONSE, COMPENSATION, AND LIABILITY ACT)

Chemical Name	Wt.%	CERCLA RQ
Ethyl Benzene	0.1	1,000

CERCLA RQ: Xylenes (RQ = 100 lbs.) conc.: 0.001 to 0.36% Ethylbenzene (RQ = 1000 lbs.) conc.: 0 to 0.072% Cumene (RQ = 5000 lbs.) conc.: 0.43 to 0.72%

TSCA (TOXIC SUBSTANCE CONTROL ACT)

Chemical Name	CAS
Stoddard solvent	8052-41-3
Ethyl Benzene	100-41-4
1,2,4-Trimethylbenzene	95-63-6

TSCA REGULATORY: This material or its components are listed in the TSCA inventory.

CALIFORNIA PROPOSITION 65: This product contains chemical (s) known to the state of California to cause cancer/birth defects

Chemical Name	Wt.%	Listed
Ethyl Benzene	0.1	Cancer

CANADA

CANADIAN ENVIRONMENTAL PROTECTION ACT: All intentional ingredients are listed on the DSL (Domestic Substance List).

DOMESTIC SUBSTANCE LIST (INVENTORY): Listed

GENERAL COMMENTS: Substances of Very High Concern - SVHC Status, Not Listed

16. OTHER INFORMATION


Date-Revised: 11/17/2017

REVISION SUMMARY: This MSDS replaces the 05/26/2015 MSDS.

HMIS RATING

HEALTH	*	1
FLAMMABILITY		2
PHYSICAL HAZARD		0
PERSONAL PROTECTION		X

NFPA CODES



ADDITIONAL MSDS INFORMATION: Caution! Can be made to burn. Treat as an OSHA/NFPA Class IIIB Combustible Liquid. Overexposure to mists or liquid may cause irritation to eyes, nose, throat, lungs and skin or aggravate a preexisting condition. Prolonged or repeated contact with skin may defat the skin and cause dermatitis. Avoid breathing mist or contact with skin and eyes.

SAFETY DATA SHEET



Date Issued : 07/21/2000
MSDS No : 210180
Date-Revised : 11/17/2017
Revision No : 16

Mineral Spirits

MANUFACTURER DISCLAIMER: The information in this SDS was obtained from sources which we believe are reliable. However, the above information is provided without warranty, expressed or implied, regarding its correctness. The conditions or methods of handling, storage, use and disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product.