

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date: 01/01/2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture

Product name : PEAK De-Icer -20 °F Windshield Wash

SDS ID : 115052

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Windshield washer fluid

1.3. Details of the supplier of the safety data sheet

Old World Industries, LLC 3100 Sanders Road Northbrook, IL 60062 - USA T (847) 559-2000 www.oldworldind.com

1.4. Emergency telephone number

Emergency number : 800 424 9300 (United States); 00 1 703 527 3887 (International)

Chemtred

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GHS-US classification

Flammable liquids, H226 Flammable liquid and vapor

Category 3

Acute toxicity (oral), H302 Harmful if swallowed.

Category 4

Acute toxicity (dermal), H311 Toxic in contact with skin.

Category 3
Acute toxicity H332

(inhalation:dust,mist)

Category 4

Specific target organ H370 Causes damage to organs (May cause blindness if swallowed)

toxicity - single exposure,

Category 1

Full text of H statements : see section 16

2.2. Label elements

GHS-US labelling

Hazard pictograms (GHS-US)





02 GHS06

Harmful if inhaled.

GHS08

Signal word (GHS-US) : Danger

Hazard statements (GHS-US) : Flammable liquid and vapor

Harmful if swallowed or if inhaled

Toxic in contact with skin.

Causes damage to organs (May cause blindness if swallowed)

Precautionary statements (GHS-US) : Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking, heat, hot surfaces, open flames, sparks

Keep container tightly closed.

Ground/Bond container and receiving equipment

Use explosion-proof electrical, lighting, ventilating equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Do not breathe mist, spray, vapors

Wash affected areas thoroughly after handling.

01/01/2024 EN (English) Page 1

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Precautionary statements (GHS-US) continued

Do not eat, drink or smoke when using this product.

Use only outdoors or in a well-ventilated area.

Wear personal protective equipment as required.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with

water/shower

If inhaled: Remove person to fresh air and keep comfortable for breathing

If exposed: Call a poison center/doctor

If swallowed: Immediately call doctor/physician or poison center. Rinse Mouth

Call doctor/physician or poison center if you feel unwell

Take off immediately all contaminated clothing and wash it before reuse. In case of fire: Use Carbon dioxide, Dry powder, foam, sand to extinguish.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container to appropriate waste disposal facility, in accordance with

local/regional/national/international regulations

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS US)

No data available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	% by wt	GHS-US classification
water (solvent)	(CAS-No.) 7732-18-5	>= 67	Not classified
methanol (solvent)	(CAS-No.) 67-56-1	<= 33	Flam. Liq. 2, H225 Acute Tox. 3 (Oral), H301 Acute Tox. 3 (Dermal), H311 Acute Tox. 3 (Inhalation), H331 STOT SE 1, H370

Full text of hazard classes and H-statements : see section 16

SECTION 4: First aid measures

	4.1. I	Description	of first aid	d measures
--	--------	-------------	--------------	------------

First-aid measures general : Never give anything by mouth to an unconscious person. If you feel unwell, seek medical

advice (show the label where possible).

First-aid measures after inhalation : If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for

breathing. Seek immediate medical advice. Allow the victim to rest. If not breathing, give

artificial respiration. If breathing is difficult, give oxygen.

First-aid measures after skin contact : Take off immediately all contaminated clothing. Rinse immediately with plenty of water (for at

least 15 minutes). If skin irritation occurs: Get medical advice/attention. Wash contaminated

clothing before reuse.

First-aid measures after eye contact : Remove contact lenses, if present and easy to do. Continue rinsing. Rinse immediately with

plenty of water for 15 minutes, lifting lower and upper lids. Take victim to an ophthalmologist if

irritation persists.

First-aid measures after ingestion : Never give anything by mouth to an unconscious person. Rinse mouth. Obtain emergency

medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation : High concentrations may cause central nervous system characterized by severe headaches,

dizziness, nausea and confusion. May cause irritation of the nose and throat.

Symptoms/effects after skin contact : Prolonged exposure to skin may cause skin irritation experienced as burning, dryness, cracking

and redness.

Symptoms/effects after eye contact : May cause severe irritation.

Symptoms/effects after ingestion : May cause nausea, abdominal pain, headache, shortness of breath, visual impairment and

blindness. Severe poisoning can lead to coma and death.

Chronic symptoms : ON CONTINUOUS/REPEATED EXPOSURE/CONTACT: Red skin, Dry skin, Skin

rash/inflammation, Headache, Feeling of weakness, Disturbed tactile sensibility, Visual disturbances, Sleeplessness, Gastrointestinal complaints, Cardiac and blood circulation effects.

01/01/2024 EN (English) 2/9

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

4.3. Indication of any immediate medical attention and special treatment needed

Methanol is metabolized to formic acid and formaldehyde. These metabolites can cause metabolic acidosis, visual disturbances and blindness. Since metabolism is required for these toxic symptoms, their onset may be delayed from 6 to 30 hours following ingestion. This product contains/consists of methanol which can cause intoxication and depression of the central nervous system.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : ABC powder. Foam. Dry powder. Carbon dioxide. Sand. Unsuitable extinguishing media : Do not use a heavy water stream. May spread fire.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Flammable liquid and vapor. Vapors are heavier than air and may travel along the ground or

may be moved by ventilation.

Explosion hazard : Heat may build pressure, rupturing closed containers, spreading fire and increasing risk of

burns and injuries.

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any

chemical fire. Prevent fire fighting water from entering the environment.

Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Do not breathe mist, spray, vapors. In case of inadequate ventilation wear respiratory

protection. Remove ignition sources. Use special care to avoid static electric charges.

6.1.1. For non-emergency personnel

Emergency procedures : Evacuate unnecessary personnel. Keep upwind. Mark the danger area.

6.1.2. For emergency responders

Protective equipment : Equip cleanup crew with proper protection.

Emergency procedures : Ventilate area.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

For containment : Contain released product, pump into suitable containers. Dam up the liquid spill. Plug the leak,

cut off the supply. Try to reduce evaporation. Take account of toxic/corrosive precipitation

water. Dilute combustible/toxic gases/vapors with water spray.

Methods for cleaning up : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect

spillage. Store away from other materials.

6.4. Reference to other sections

For further information refer to section 13. For further information refer to section 8: "Exposure controls/personal protection".

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed : In use, may form flammable vapor-air mixture.

Precautions for safe handling : Wash hands and other exposed areas with mild soap and water before eating, drinking or

smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor.

of vapor

Hygiene measures : Wash contaminated clothing before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Use explosion-proof ventilating, lighting, electrical equipment. Ground/bond container and

receiving equipment. Proper grounding procedures to avoid static electricity should be followed.

Storage conditions : Keep only in the original container in a cool, well ventilated place away from : Heat sources, hot surfaces, open flames, sparks. Keep container closed when not in use. Do not store near food,

foodstuffs, drugs or potable water supplies. Do not cut, drill, weld, use a blowtorch on, etc. containers even when empty.

Variable from the manifest of the manifest of

Incompatible products : Keep away from strong acids, strong bases and oxidizing agents.

Incompatible materials : Sources of ignition.

01/01/2024 EN (English) 3/9

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

methanol (67-56-1)			
ACGIH	Local name	Methanol	
ACGIH	ACGIH TWA (ppm)	200 ppm (Skin)	
ACGIH	ACGIH STEL (ppm)	250 ppm (Skin)	
ACGIH	Remark (ACGIH)	Headache; eye dam; dizziness; nausea	
OSHA	OSHA PEL (TWA) (mg/m³)	260 mg/m³ (Skin)	
OSHA	OSHA PEL (TWA) (ppm)	200 ppm (Skin)	

water (7732-18-5)

Not applicable

8.2. Appropriate engineering controls

No additional information available

8.3. Individual protection measures/Personal protective equipment

Personal protective equipment:

Avoid all unnecessary exposure. Gloves. Safety glasses.

Hand protection:

Wear protective gloves.

Eye protection:

Chemical goggles or safety glasses

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

In case of inadequate ventilation wear respiratory protection. Wear appropriate mask





Other information:

Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid
Color : Blue
Odor : alcohol

Odor threshold : No data available

Relative evaporation rate (butylacetate=1) : Greater than n-butyl acetate

Freezing point : $-28.9 \,^{\circ}\text{C} \, (-20 \,^{\circ}\text{F})$ Boiling point : $81.7 \,^{\circ}\text{C} \, (179 \,^{\circ}\text{F})$ Flash point : $33.3 \,^{\circ}\text{C} \, (92 \,^{\circ}\text{F})$ Auto-ignition temperature : No data available

01/01/2024 EN (English) 4/9

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Decomposition temperature : No data available Flammability (solid, gas) : No data available Vapor pressure : 43 mm Hg @ 20 °C Relative vapor density at 20 °C : Heavier than air Specific Gravity 0.96 @ 20 °C Solubility : Water: Complete Log Pow : No data available Log Kow : No data available Viscosity, kinematic : No data available No data available Viscosity, dynamic Explosive limits : 6 - 36 vol % Explosive properties : No data available Oxidizing properties : No data available

9.2. Other information

VOC content : < 33 %

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

10.5. Incompatible materials

Keep away from strong acids, strong bases and oxidizing agents.

10.6. Hazardous decomposition products

Fume. Carbon monoxide. Carbon dioxide.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

methanol (67-56-1)	
LD50 oral rat	1187 - 2769 mg/kg bodyweight (BASF test, Rat, Male / female, Weight of evidence, Aqueous solution, Oral, 7 day(s))
LD50 dermal rabbit	17100 mg/kg (Rabbit, Inconclusive, insufficient data, Dermal)
LC50 inhalation rat (mg/l)	128.2 mg/l/4h (BASF test, 4 h, Rat, Male/female, Weight of evidence)
ATE US (oral)	100 mg/kg bodyweight
ATE US (dermal)	300 mg/kg bodyweight
ATE US (gases)	700 ppmv/4h
ATE US (vapors)	3 mg/l/4h
ATE US (dust,mist)	0.5 mg/l/4h

 Skin corrosion/irritation
 : Not classified

 Serious eye damage/irritation
 : Not classified

 Respiratory or skin sensitisation
 : Not classified

 Germ cell mutagenicity
 : Not classified

 Carcinogenicity
 : Not classified

Reproductive toxicity : Not classified

STOT-single exposure : Causes damage to organs (May cause blindness if swallowed) .

STOT-repeated exposure : Not classified

01/01/2024 EN (English) 5/9

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Aspiration hazard : Not classified

Symptoms/effects after inhalation : High concentrations may cause central nervous system characterized by severe headaches,

dizziness, nausea and confusion. May cause irritation of the nose and throat.

Symptoms/effects after skin contact : Prolonged exposure to skin may cause skin irritation experienced as burning, dryness, cracking

and redness.

Symptoms/effects after eye contact : May cause severe irritation.

Symptoms/effects after ingestion : May cause nausea, abdominal pain, headache, shortness of breath, visual impairment and

blindness. Severe poisoning can lead to coma and death.

Chronic symptoms : ON CONTINUOUS/REPEATED EXPOSURE/CONTACT: Red skin, Dry skin, Skin

rash/inflammation, Headache, Feeling of weakness, Disturbed tactile sensibility, Visual

disturbances, Sleeplessness, Gastrointestinal complaints, Cardiac and blood circulation effects.

SECTION 12: Ecological information

12.1. Toxicity

methanol (67-56-1)	
LC50 fish 1	15,400.00 mg/l (EPA 660/3 - 75/009, 96 h, Lepomis macrochirus, Flow-through system, Fresh water, Experimental value, Lethal)
EC50 Daphnia 1	18,260.00 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 96 h, Daphnia magna, Semi-static system, Fresh water, Experimental value, Locomotor effect)
ErC50 (algae)	22,000.00 mg/l (OECD 201: Alga, Growth Inhibition Test, 96 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value)

12.2. Persistence and degradability

methanol (67-56-1)		
Persistence and degradability Readily biodegradable in the soil. Readily biodegradable in water.		
Biochemical oxygen demand (BOD) $0.6 - 1.12 \text{ g } O_2/\text{g substance}$		
Chemical oxygen demand (COD) 1.42 g O ₂ /g substance		
ThOD 1.50 g O ₂ /g substance		

12.3. Bioaccumulative potential

methanol (67-56-1)		
BCF fish 1	1 - 4.5 (72 h, Cyprinus carpio, Static system, Fresh water, Experimental value)	
Log Pow -0.77 (Experimental value)		
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).	

12.4. Mobility in soil

methanol (67-56-1)		
Surface tension	0.02 N/m (20 °C)	
Log Koc	0.09 (log Koc, SRC PCKOCWIN v2.0, Calculated value)	
Ecology - soil	Highly mobile in soil.	

12.5. Other adverse effects

Effect on the ozone layer : No known effect on the ozone layer

Other information : Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product/Packaging disposal recommendations : Dispose of contents/container to appropriate waste disposal facility, in accordance with

local/regional/national/international regulations.

Ecology - waste materials : Avoid release to the environment.

SECTION 14: Transport information

01/01/2024 EN (English) 6/9

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Department of Transportation (DOT)

In accordance with DOT

Non-Bulk:

In inner packaging no more than 5.0 L (1.3 Gallons): Proper Shipping Name: Limited Quantity of Class III Per 49 CFR Part 173.150 (PG III, inner packaging no more than 5.0L)

Bulk (in quanitites larger than 5.0L [1.3 gallons] in a single container)

Transport document description : UN1993 Flammable liquids, n.o.s., 3, III

UN-No.(DOT) : UN1993

Proper Shipping Name (DOT) : Flammable liquids, n.o.s.

Class (DOT) : 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120

Packing group (DOT) : III - Minor Danger Hazard labels (DOT) : 3 - Flammable liquid



DOT Packaging Non Bulk (49 CFR 173.xxx) : 203 DOT Packaging Bulk (49 CFR 173.xxx) : 242

DOT Symbols : G - Identifies PSN requiring a technical name

DOT Packaging Exceptions (49 CFR 173.xxx) : 150 DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 : 220 L

CFR 175.75)

DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a

passenger vessel.

Emergency Response Guide (ERG) Number

: No supplementary information available. Other information

Transportation of Dangerous Goods

Refer to current TDG Canada for further Canadian regulations

Transport by sea

In accordance with IMDG / IMO

Transport document description (IMDG) : UN 1992 Flammable Liquid, Toxic, n.o.s. (methanol), 3, III

UN-No. (IMDG) : 1992

Proper Shipping Name (IMDG) : Flammable Liquid, Toxic, n.o.s. (methanol)

Class (IMDG) : 3 - Flammable liquids

Packing group (IMDG) : III - substances presenting low danger

Air transport

In accordance with IATA / ICAO

Transport document description (IATA) : UN 1992 Flammable Liquid, Toxic, n.o.s. (methanol), 3 (6.1), III

UN-No. (IATA)

Proper Shipping Name (IATA) : Flammable Liquid, Toxic, n.o.s. (methanol)

Class (IATA) : 3 - Flammable Liquids Packing group (IATA) : III - Minor Danger Subsidiary risks (IATA) : 6.1 - Toxic substances

SECTION 15: Regulatory information

15.1. US Federal regulations

01/01/2024 EN (English) 7/9

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

PEAK De-Icer -20 °F Windshield Wash		
EPA TSCA Regulatory Flag	Toxic Substances Control Act (TSCA): The intentional ingredients of this product are listed	
SARA Section 302 Threshold Planning Quantity (TPQ)	None	
SARA Section 311/312 Hazard Classes	Delayed (chronic) health hazard Fire hazard Immediate (acute) health hazard	
SARA Section 313 - Emission Reporting	33 % (Methanol CAS # 67-56-1)	

methanol (67-56-1)		
CERCLA RQ 5000 lb(s) (2270 kg)		
water (7732-18-5)		
Listed on the United States TSCA (Toxic Substances Control Act) inventory		

15.2. International regulations

CANADA

PEAK De-Icer -20 °F Windshield Wash	
WHMIS Classification	This SDS has been prepared according to the criteria of the Hazardous Products Regulations (HPR) (WHMIS 2015) and the SDS contains all of the information required by the HPR. Applicable GHS information is listed in section 2.2 of this SDS.

15.3. US State regulations

MARNING:

This product can expose you to methanol, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

methanol (67-56-1)					
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)	Maximum allowable dose level (MADL)
No	Yes	No	No		47000 μg/day (inhalation); 23,000 μg/day (oral)

methanol (67-56-1)

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) List

SECTION 16: Other information

Revision date : 01/01/2024

Full text of H-statements:

H225	Highly flammable liquid and vapor
H226	Flammable liquid and vapor
H301	Toxic if swallowed.
H302	Harmful if swallowed.
H311	Toxic in contact with skin.
H331	Toxic if inhaled.
H332	Harmful if inhaled.
H370	Causes damage to organs

01/01/2024 EN (English) 8/9

Safety Data Sheet

NFPA reactivity

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

NFPA health hazard : 1 - Materials that, under emergency conditions, can cause significant

irritation

NFPA fire hazard : 3 - Liquids and solids (including finely divided suspended solids) that can be ignited under almost all ambient temperature conditions.

: 0 - Material that in themselves are normally stable, even under fire



SDS GHS US (GHS HazCom 2012) OWI

Old World Industries, LLC makes no warranty, representation or guarantee as to the accuracy, sufficiency or completeness of the material set forth herein. It is the user's responsibility to determine the safety, toxicity and suitability of his own use, handling and disposal of this product. Since actual use by others is beyond our control, no warranty, expressed or implied, is made by Old World Industries, LLC as to the effects of such use, the results to be obtained or the safety and toxicity of this product, nor does Old World Industries, LLC assume liability arising out of the use by others of this product referred to herein. The data in this SDS relates only to the specific material designated herein and does not relate to use in combination with any other material or in any process.

01/01/2024 EN (English) 9/9