



# JOHNSEN'S R134A 30 LB CYLINDER

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date: 01/30/2017

Supersedes:09/02/2015

Version: 1.2

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product form : Substance  
Trade name : JOHNSEN'S R134A 30 LB CYLINDER  
Product code : 6330

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Refrigerant

#### 1.3. Details of the supplier of the safety data sheet

Technical Chemical Company  
P.O. BOX 139  
Cleburne, Texas 76033  
T 817-645-6088

#### 1.4. Emergency telephone number

Emergency number : CHEMTREC 24 Hour 1-800-424-9300, 1-703-527-3887 (International)

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### GHS-US classification

Liquefied gas H280

Full text of H statements : see section 16

#### 2.2. Label elements

##### GHS-US labeling

Hazard pictograms (GHS-US) :



GHS04

Signal word (GHS-US) : Warning  
Hazard statements (GHS-US) : H280 - Contains gas under pressure; may explode if heated  
Precautionary statements (GHS-US) : P410+P403 - Protect from sunlight. Store in a well-ventilated place  
P251 - Pressurized container: Do not pierce or burn, even after use  
P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F  
P501 - Dispose of contents/container to appropriate waste disposal facility, in accordance with local, regional, national, international regulations.

#### 2.3. Other hazards

Other hazards not contributing to the classification : Contains gas under pressure; may explode if heated. Intentional misuse and inhalation abuse may cause cardiac or central nervous systems effects. Warning. May Cause frostbite in contact with skin. May Cause frostbite in contact with skin. (Liquid form can be ejected if the aerosol can is not held upright during use.) Warning. This product dispenses liquid. Liquid may drip onto skin causing frostbite, blistering, red skin. WARNING. . Asphyxiant in high concentrations.

#### 2.4. Unknown acute toxicity (GHS US)

No data available

### SECTION 3: Composition/Information on ingredients

#### 3.1. Substance

Name : 1,1,1,2-Tetrafluoroethane

| Name                      | Product identifier | %    | GHS-US classification |
|---------------------------|--------------------|------|-----------------------|
| 1,1,1,2-Tetrafluoroethane | (CAS No) 811-97-2  | > 99 | Liquefied gas, H280   |

Full text of H-phrases: see section 16

#### 3.2. Mixture

Not applicable

The exact percentage is a trade secret.

# JOHNSEN'S R134A 30 LB CYLINDER

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

|                                       |   |
|---------------------------------------|---|
| First-aid measures general            | : Check the vital functions. Unconscious: maintain adequate airway and respiration. Respiratory arrest: artificial respiration or oxygen. Cardiac arrest: perform resuscitation. Victim conscious with laboured breathing: half-seated. Victim in shock: on his back with legs slightly raised. Vomiting: prevent asphyxia/aspiration pneumonia. Prevent cooling by covering the victim (no warming up). Keep watching the victim. Give psychological aid. Keep the victim calm, avoid physical strain. Depending on the victim's condition: doctor/hospital. |
| First-aid measures after inhalation   | : Remove the victim into fresh air. Respiratory problems: consult a doctor/medical service.   |
| First-aid measures after skin contact | : Rinse with water. Take victim to a doctor if irritation persists. In case of frostbites: Wash immediately with lots of water (15 minutes)/shower. Do not apply (chemical) neutralizing agents. Remove clothing while washing. Do not remove clothing if it sticks to the skin. Cover wounds with sterile bandage. Consult a doctor/medical service. If burned surface > 10%: take victim to hospital.   |
| First-aid measures after eye contact  | : Rinse immediately with plenty of water for 15 minutes. Do not apply neutralizing agents. Take victim to an ophthalmologist.   |
| First-aid measures after ingestion    | : Not applicable.   |

#### 4.2. Most important symptoms and effects, both acute and delayed

|                                      |   |
|--------------------------------------|---|
| Symptoms/injuries                    | : Not expected to present a significant hazard under anticipated conditions of normal use.  |
| Symptoms/injuries after inhalation   | : EXPOSURE TO HIGH CONCENTRATIONS: Accelerated heart action. Disturbances of heart rate. Coordination disorders. Feeling of weakness. Respiratory difficulties. Vomiting. Nausea. Disturbances of consciousness. Risk of lung oedema. Respiratory collapse. |
| Symptoms/injuries after skin contact | : Red skin. Blisters. Frostbites.   |
| Symptoms/injuries after eye contact  | : Not applicable.   |
| Symptoms/injuries after ingestion    | : Not applicable.   |
| Chronic symptoms                     | : No effects known.   |

#### 4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

|                                |  |
|--------------------------------|--|
| Suitable extinguishing media   | : Foam. Dry powder. Carbon dioxide. Water spray. Sand. |
| Unsuitable extinguishing media | : Do not use a heavy water stream.                     |

#### 5.2. Special hazards arising from the substance or mixture

|            |  |
|------------|--|
| Reactivity | : On burning: release of toxic and corrosive gases/vapours (hydrofluoric acid, carbon monoxide - carbon dioxide, carbonyl fluoride). Reacts with (some) acids. |
|------------|--|

#### 5.3. Advice for firefighters

|                                |   |
|--------------------------------|---|
| Firefighting instructions      | : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire-fighting water from entering environment. |
| Protection during firefighting | : Do not enter fire area without proper protective equipment, including respiratory protection.   |
| Other information              | : NFPA Aerosol Level 1.   |

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

|                  |                  |
|------------------|------------------|
| General measures | : Evacuate area. |
|------------------|------------------|

##### 6.1.1. For non-emergency personnel

|                      |   |
|----------------------|---|
| Protective equipment | : Gloves. Insulating gloves. Protective clothing. Safety glasses. |
| Emergency procedures | : Evacuate unnecessary personnel.                                 |

##### 6.1.2. For emergency responders

|                      |  |
|----------------------|--|
| Protective equipment | : Equip cleanup crew with proper protection. |
| Emergency procedures | : Ventilate area.                            |

#### 6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

#### 6.3. Methods and material for containment and cleaning up

|                         |   |
|-------------------------|---|
| For containment         | : Contain released substance, pump into suitable containers. Plug the leak, cut off the supply. Tip the container on one side to stop the leakage. Do not spray water on unheated tank walls. |
| Methods for cleaning up | : Store away from other materials.  |

#### 6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

# JOHNSEN'S R134A 30 LB CYLINDER

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

|                                   |  |
|-----------------------------------|--|
| Additional hazards when processed | : Pressurized container: Do not pierce or burn, even after use.  |
| Precautions for safe handling     | : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor.  |
| Hygiene measures                  | : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Wash contaminated clothing before reuse. Wash affected areas thoroughly after handling. Do not eat, drink or smoke when using this product. Always wash hands after handling the product. Remove contaminated clothes. Separate working clothes from town clothes. Launder separately. |

#### 7.2. Conditions for safe storage, including any incompatibilities

|                        |   |
|------------------------|---|
| Storage conditions     | : Keep only in the original container in a cool, well ventilated place away from : Keep container closed when not in use. |
| Incompatible products  | : Strong bases. Strong acids.   |
| Incompatible materials | : Sources of ignition. Direct sunlight.   |
| Storage area           | : Store in a well-ventilated place.   |

#### 7.3. Specific end use(s)

Follow Label Directions.

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

#### 8.2. Exposure controls

|                                  |  |
|----------------------------------|--|
| Appropriate engineering controls | : Local exhaust ventilation, vent hoods . Ensure good ventilation of the work station. |
| Personal protective equipment    | : Gloves. Safety glasses. Avoid all unnecessary exposure.                              |



|                                   |   |
|-----------------------------------|---|
| Materials for protective clothing | : GIVE GOOD RESISTANCE: neoprene. butyl rubber. |
| Hand protection                   | : Wear protective gloves.                       |
| Eye protection                    | : Chemical goggles or safety glasses.           |
| Skin and body protection          | : Wear suitable protective clothing.            |
| Respiratory protection            | : Wear appropriate mask.                        |
| Environmental exposure controls   | : Avoid release to the environment.             |
| Consumer exposure controls        | : Avoid contact during pregnancy/while nursing. |
| Other information                 | : Do not eat, drink or smoke during use.        |

### SECTION 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

|   |                       |
|---|-----------------------|
| Physical state                              | : Gas                 |
| Appearance                                  | : Liquefied gas.      |
| Molecular mass                              | : 102.03 g/mol        |
| Color                                       | : Colourless.         |
| Odor  | : Ether-like odour.   |
| Odor threshold                              | : No data available   |
| pH  | : No data available   |
| Relative evaporation rate (butyl acetate=1) | : No data available   |
| Melting point                               | : -101 °C             |
| Freezing point                              | : No data available   |
| Boiling point                               | : -26 °C              |
| Flash point                                 | : No data available   |
| Critical temperature                        | : 101 °C              |
| Auto-ignition temperature                   | : > 743 °C            |
| Decomposition temperature                   | : 368 °C              |
| Flammability (solid, gas)                   | : No data available   |
| Vapor pressure                              | : 6661 hPa @ 25 deg C |
| Vapor pressure at 50 °C                     | : 13190 hPa           |

# JOHNSEN'S R134A 30 LB CYLINDER

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

|                                 |   |
|---------------------------------|---|
| Critical pressure               | : 40560 hPa   |
| Relative vapor density at 20 °C | : < 3.52 @ 20 deg C   |
| Relative density                | : 1.2 @ -27 deg C   |
| Specific gravity / density      | : 1206 kg/m <sup>3</sup> @ -27 deg C  |
| Solubility                      | : Poorly soluble in water. Soluble in ethanol. Soluble in ether. Soluble in hexane.<br>Water: 0.15 g/100ml @ 25 deg C |
| Log Pow                         | : 1.06 (OECD 107: Partition Coefficient (n-octanol/water): Shake Flask Method)  |
| Log Kow                         | : No data available   |
| Viscosity, kinematic            | : No data available   |
| Viscosity, dynamic              | : No data available   |
| Explosive properties            | : No data available   |
| Oxidizing properties            | : No data available   |
| Explosion limits                | : No data available   |

### 9.2. Other information

|             |   |
|-------------|---|
| VOC content | : 100 % VOC Exempt  |
| Gas group   | : Gas/vapour heavier than air at 20°C. Substance has neutral reaction. May generate electrostatic charges |

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

On burning: release of toxic and corrosive gases/vapours (hydrofluoric acid, carbon monoxide - carbon dioxide, carbonyl fluoride). Reacts with (some) acids.

### 10.2. Chemical stability

Not established.

### 10.3. Possibility of hazardous reactions

Not established.

### 10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures.

### 10.5. Incompatible materials

Strong acids. Strong bases.

### 10.6. Hazardous decomposition products

Toxic fume. . Carbon monoxide. Carbon dioxide.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity : Not classified

| 1,1,1,2-Tetrafluoroethane (811-97-2)                |   |
|---|---|
| LC50 inhalation rat (mg/l)                          | > 2000 mg/l/4h (Rat; Literature study)  |
| LC50 inhalation rat (ppm)                           | > 359300 ppm/4h (Rat; Literature study)   |
| Skin corrosion/irritation                           | : Not classified  |
| Serious eye damage/irritation                       | : Not classified  |
| Respiratory or skin sensitization                   | : Not classified  |
| Germ cell mutagenicity                              | : Not classified  |
| Carcinogenicity                                     | : Not classified  |
| Reproductive toxicity                               | : Not classified  |
| Specific target organ toxicity (single exposure)    | : Not classified  |
| Specific target organ toxicity (repeated exposure)  | : Not classified  |
| Aspiration hazard                                   | : Not classified  |
| Potential Adverse human health effects and symptoms | : Based on available data, the classification criteria are not met.   |
| Symptoms/injuries after inhalation                  | : EXPOSURE TO HIGH CONCENTRATIONS: Accelerated heart action. Disturbances of heart rate. Coordination disorders. Feeling of weakness. Respiratory difficulties. Vomiting. Nausea. Disturbances of consciousness. Risk of lung oedema. Respiratory collapse. |
| Symptoms/injuries after skin contact                | : Red skin. Blisters. Frostbites.   |
| Symptoms/injuries after eye contact                 | : Not applicable.   |

# JOHNSEN'S R134A 30 LB CYLINDER

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Symptoms/injuries after ingestion : Not applicable.  
Chronic symptoms : No effects known.

### SECTION 12: Ecological information

#### 12.1. Toxicity

| 1,1,1,2-Tetrafluoroethane (811-97-2) |                       |
|--------------------------------------|-----------------------|
| LC50 fish 1                          | 450 mg/l (LC50; 96 h) |
| EC50 Daphnia 1                       | 980 mg/l (EC50; 48 h) |

#### 12.2. Persistence and degradability

| JOHNSEN'S R134A 30 LB CYLINDER |                  |
|--------------------------------|------------------|
| Persistence and degradability  | Not established. |

| 1,1,1,2-Tetrafluoroethane (811-97-2) |                                     |
|--------------------------------------|-------------------------------------|
| Persistence and degradability        | Not readily biodegradable in water. |

#### 12.3. Bioaccumulative potential

| JOHNSEN'S R134A 30 LB CYLINDER |  |
|--------------------------------|--|
| Log Pow                        | 1.06 (OECD 107: Partition Coefficient (n-octanol/water): Shake Flask Method) |
| Bioaccumulative potential      | Not established.   |

| 1,1,1,2-Tetrafluoroethane (811-97-2) |  |
|--------------------------------------|--|
| BCF other aquatic organisms 1        | 5 - 58 (BCF)   |
| Log Pow                              | 1.06 (OECD 107: Partition Coefficient (n-octanol/water): Shake Flask Method) |
| Bioaccumulative potential            | Low potential for bioaccumulation (BCF < 500).                               |

#### 12.4. Mobility in soil

No additional information available

#### 12.5. Other adverse effects

Other information : Avoid release to the environment.

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations.  
Ecology - waste materials : Avoid release to the environment.

### SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

US DOT (ground): UN3159, 1,1,1,2-Tetrafluoroethane, 2.2  
ICAO/IATA (air): UN3159, 1,1,1,2-Tetrafluoroethane, 2.2  
IMO/IMDG (water): UN3159, 1,1,1,2-Tetrafluoroethane, 2.2  
Special Provisions: T50 - When portable tank instruction T50 is referenced in Column (7) of the 172.101 Table, the applicable liquefied compressed gases are authorized to be transported in portable tanks in accordance with the requirements of 173.313 of this subchapter

#### 14.2. UN proper shipping name

Proper Shipping Name (DOT) : 1,1,1,2-Tetrafluoroethane  
Class (DOT) : 2.2 - Class 2.2 - Non-flammable compressed gas 49 CFR 173.115  
Hazard labels (DOT) : 2.2 - Non-flammable gas



DOT Special Provisions (49 CFR 172.102) : T50 - When portable tank instruction T50 is referenced in Column (7) of the 172.101 Table, the applicable liquefied compressed gases are authorized to be transported in portable tanks in accordance with the requirements of 173.313 of this subchapter  
DOT Packaging Exceptions (49 CFR 173.xxx) : 306  
DOT Packaging Non Bulk (49 CFR 173.xxx) : 304  
DOT Packaging Bulk (49 CFR 173.xxx) : 314;315

#### 14.3. Additional information

Other information : No supplementary information available.

# JOHNSEN'S R134A 30 LB CYLINDER

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### Overland transport

No additional information available

### Transport by sea

DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel

### Air transport

DOT Quantity Limitations Passenger aircraft/rail : 75 kg  
(49 CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 : 150 kg  
CFR 175.75)

## SECTION 15: Regulatory information

### 15.1. US Federal regulations

#### JOHNSEN'S R134A 30 LB CYLINDER

Listed on the United States TSCA (Toxic Substances Control Act) inventory

|                                     |  |
|-------------------------------------|--|
| SARA Section 311/312 Hazard Classes | Immediate (acute) health hazard<br>Sudden release of pressure hazard |
|-------------------------------------|--|

#### 1,1,1,2-Tetrafluoroethane (811-97-2)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

|                                     |  |
|-------------------------------------|--|
| SARA Section 311/312 Hazard Classes | Sudden release of pressure hazard<br>Immediate (acute) health hazard |
|-------------------------------------|--|

### 15.2. International regulations

#### CANADA

#### JOHNSEN'S R134A 30 LB CYLINDER

|                      |                          |
|----------------------|--------------------------|
| WHMIS Classification | Class A - Compressed Gas |
|----------------------|--------------------------|

#### 1,1,1,2-Tetrafluoroethane (811-97-2)

|                      |                          |
|----------------------|--------------------------|
| WHMIS Classification | Class A - Compressed Gas |
|----------------------|--------------------------|

### EU-Regulations

No additional information available

### Classification according to Regulation (EC) No. 1272/2008 [CLP]

Not classified

### Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

Not classified

### 15.2.2. National regulations

No additional information available

### 15.3. US State regulations

#### JOHNSEN'S R134A 30 LB CYLINDER

|   |    |
|---|----|
| U.S. - California - Proposition 65 - Carcinogens List | No |
|---|----|

|   |    |
|---|----|
| U.S. - California - Proposition 65 - Developmental Toxicity | No |
|---|----|

|   |    |
|---|----|
| U.S. - California - Proposition 65 - Reproductive Toxicity - Female | No |
|---|----|

|   |    |
|---|----|
| U.S. - California - Proposition 65 - Reproductive Toxicity - Male | No |
|---|----|

#### 1,1,1,2-Tetrafluoroethane (811-97-2)

| U.S. - California - Proposition 65 - Carcinogens List | U.S. - California - Proposition 65 - Developmental Toxicity | U.S. - California - Proposition 65 - Reproductive Toxicity - Female | U.S. - California - Proposition 65 - Reproductive Toxicity - Male | Non-significant risk level (NSRL) |
|---|---|---|---|-----------------------------------|
| No  | No  | No  | No  |                                   |

## SECTION 16: Other information

Other information : None.

# JOHNSEN'S R134A 30 LB CYLINDER

## Safety Data Sheet


according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Full text of H-phrases:

H280

Contains gas under pressure; may explode if heated

NFPA health hazard : 1 - Exposure could cause irritation but only minor residual injury even if no treatment is given.  
NFPA fire hazard : 0 - Materials that will not burn.  
NFPA reactivity : 1 - Normally stable, but can become unstable at elevated temperatures and pressures or may react with water with some release of energy, but not violently.



### HMIS III Rating

Health : 1 Slight Hazard - Irritation or minor reversible injury possible  
Flammability : 0 Minimal Hazard  
Physical : 1 Slight Hazard  
Personal Protection : B

SDS US (GHS HazCom 2012) - TCC

*The Supplier identified in Section 1 of this SDS has evaluated this product and certifies it to be labeled and packaged in compliance with the applicable provisions of the Federal Hazardous Substance Act as stated in 16 CFR 1500 and enforced by the Consumer Product Safety Commission, and where applicable the products that require Child Resistant Closures are packaged in accordance with the Poison Prevention Packaging Act as stated in 16 CFR 1700 and enforced by the Consumer Product Safety Commission. All closures have been tested in accordance with the latest protocols. No other testing is required to certify compliance with the above. The date of manufacture is stamped on the product*

*Disclaimer: The information and recommendations contained herein are based upon tests believed to be reliable. However, the manufacturer/distributor of this product does not guarantee their accuracy or completeness NOR SHALL ANY OF THIS INFORMATION CONSTITUTE A WARRANTY, WHETHER EXPRESSED OR IMPLIED, AS TO THE SAFETY OF THE GOODS, THE MERCHANTABILITY OF THE GOODS, OR THE FITNESS OF THE GOODS FOR A PARTICULAR PURPOSE. Adjustment to conform to actual conditions of usage may be required. The manufacturer/distributor assumes no responsibility for results obtained or for incidental or consequential damages, including lost profits, arising from the use of these data. No warranty against infringement of any patent, copyright or trademark is made or implied.*