

SAFETY DATA SHEET



Date Issued : 07/18/2000
 MSDS No : 210090
 Date-Revised : 12/19/2017
 Revision No : 9

Rule 66 Quick Dry

1. PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: Rule 66 Quick Dry
PRODUCT DESCRIPTION: Rule 66 Quick Dry
PRODUCT CODE: 210090
PRODUCT FORMULATION NAME: Rule 66 Quick Dry
CHEMICAL FAMILY: Aliphatic Petroleum Hydrocarbons
MOLECULAR FORMULA: Mixture
GENERIC NAME: Petroleum-Naphtha
ACTIVE INGREDIENT(S): Stoddard solvent

DISTRIBUTOR

AMERICHEM SALES COMPANY LLC
 340 NORTH ST.
 MASON, MI 48854
Emergency Phone: 517-676-9363

24 HR. EMERGENCY TELEPHONE NUMBERS

CHEMTREC (U.S.): (800) 424-9300
CANUTEC (613) 996-6666

COMMENTS: To the best of our knowledge, this Safety Data Sheet conforms to the requirements of US OSHA 29 CFR 1910.1200, 91/155/EEC and Canadian Hazardous Products Act.

2. HAZARDS IDENTIFICATION

GHS CLASSIFICATIONS

Health:

Aspiration Hazard, Category 1
 Skin Irritation, Category 2
 Target Organ Toxicity (Single exposure), Category 3

Environmental:

Aquatic Toxicity (Acute), Category 3
 Aquatic Toxicity (Chronic), Category 3

Physical:

Flammable Liquids, Category 3

GHS LABEL



Flammable
Liquid



Health
hazard



Exclamation
mark

SIGNAL WORD: DANGER

HAZARD STATEMENTS

H226: Flammable liquid and vapour.
 H315: Causes skin irritation.
 H304: May be fatal if swallowed and enters airways.
 H336: May cause drowsiness or dizziness.
 H412: Harmful to aquatic life with long lasting effects.

Precautionary statement(s)

SAFETY DATA SHEET



Date Issued : 07/18/2000
 MSDS No : 210090
 Date-Revised : 12/19/2017
 Revision No : 9

Rule 66 Quick Dry

Prevention:

- P280: Wear protective gloves/protective clothing/eye protection/face protection.
- P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P241: Use explosion-proof [electrical/ventilating/lighting/...] equipment.
- P242: Use non-sparking tools.
- P243: Take action to prevent static discharges.
- P233: Keep container tightly closed.
- P271: Use only outdoors or in a well-ventilated area.
- P261: Avoid breathing dust/fume/gas/mist/vapours/spray.
- P264: Wash ... thoroughly after handling.
- P273: Avoid release to the environment.

Response:

- P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.
- P312: Call a POISON CENTER/doctor/...if you feel unwell.
- P308+P313: IF exposed or concerned: Get medical advice/ attention.
- P301+P312: IF SWALLOWED: Call a POISON CENTER/ doctor/...if you feel unwell.
- P331: Do NOT induce vomiting.
- P303+P361+P353: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
- P302+P352: IF ON SKIN: Wash with plenty of water/...
- P332+P313: If skin irritation occurs: Get medical advice/attention.
- P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P337+P313: If eye irritation persists: Get medical advice/attention.

Storage:

- P405: Store locked up.
- P403+P235: Store in a well-ventilated place. Keep cool.

Disposal:

- P501: Dispose of contents/container in accordance with local regulations.

EMERGENCY OVERVIEW

PHYSICAL APPEARANCE: Clear, Colorless liquid.

IMMEDIATE CONCERNS: CAUTION! May cause eye and skin irritation.

POTENTIAL HEALTH EFFECTS

EYES: May cause moderate burning, tearing, redness and swelling.

SKIN: Moderate irritation and discomfort. Defatting of skin and redness are possible. Toxic systemic effects from absorption are expected to be minor.

INGESTION: Gastrointestinal tract irritation and/or discomfort is possible.

INHALATION: Moderate respiratory discomfort and/or headaches. Toxic systemic effects from inhalation are expected to be minor.

ROUTES OF ENTRY: Absorption, Inhalation, Ingestion

COMMENTS: Hazards Not Otherwise Classified (HNOC): None as defined under 29 CFR 1910.1200.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	Wt.%	CAS
Stoddard solvent	100	8052-41-3

SAFETY DATA SHEET



Date Issued : 07/18/2000
MSDS No : 210090
Date-Revised : 12/19/2017
Revision No : 9

Rule 66 Quick Dry

4. FIRST AID MEASURES

EYES: Immediately flush eyes with plenty of water for 15 minutes. If irritation persists, seek medical attention.

SKIN: Wash exposed area with mild soap and water. Get medical attention if irritation develops or persists.

INGESTION: Do not induce vomiting. Danger from aspirating into lungs exceeds short term toxic effects. Get immediate medical help.

INHALATION: Remove victim from area of exposure. If unconscious, give oxygen. Give artificial respiration if not breathing. Get immediate medical attention.

5. FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA: Use dry chemical, foam, or carbon dioxide.

EXPLOSION HAZARDS: Vapor accumulations may flash and/or explode if ignited. Keep ignition sources, open flames, ect., away from these fumes.

FIRE FIGHTING PROCEDURES: Proper respiratory equipment to protect against the hazardous effects of combustion products is recommended. Water in a straight hose stream may cause fire to spread and should be used as a cooling medium only.

6. ACCIDENTAL RELEASE MEASURES

SMALL SPILL: Extinguish possible sources of ignition. Evacuate all unprotected personnel and ventilate area. Only personnel equipped with proper respiratory, skin/eye protection should enter spill area. Dike area to contain spill and clean up by absorbing on an inert absorbant or other means. Don't flush into sewers or natural waterways.

LARGE SPILL: Contain material as described above and call the local fire or police department for immediate emergency assistance.

7. HANDLING AND STORAGE

GENERAL PROCEDURES: Do not store with Oxidizing agents.

HANDLING: Store in a cool, dry, ventilated area away from excessive heat, sparks and open flames. Avoid prolonged or repeated contact with skin and/or breathing of vapors when handling. Keep containers closed when not in use.

STORAGE: Store unopened containers under cool, dry and ventilated conditions. Keep away from heat, sparks and flame.

STORAGE TEMPERATURE: SHOULD BE STORED IN A COOL DRY PLACE.

STORAGE PRESSURE: AMBIENT

SHELF LIFE: THE SHELF LIFE OF THIS PRODUCT IS UNDETERMINED, BUT MAY BECOME SUSPECT ONE YEAR FROM THE DATE OF PURCHASE.

ELECTROSTATIC ACCUMULATION HAZARD: When transferring this product, there is potential for the accumulation of static electricity. Consideration should be given to bonding and grounding of equipment during loading, unloading, and transfer of this product.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

SAFETY DATA SHEET



Date Issued : 07/18/2000
 MSDS No : 210090
 Date-Revised : 12/19/2017
 Revision No : 9

Rule 66 Quick Dry

EXPOSURE GUIDELINES

OSHA HAZARDOUS COMPONENTS (29 CFR1910.1200)				
EXPOSURE LIMITS				
Chemical Name	Type		ppm	mg/m ³
Stoddard solvent	OSHA PEL	TWA	500 ppm	2900 mg/m ³
		STEL	ppm	mg/m ³
	ACGIH TLV	TWA	100 ppm	572 mg/m ³
		STEL	ppm	mg/m ³
	Supplier OEL	TWA	NL	NL
		STEL	NL	NL

ENGINEERING CONTROLS: If current ventilation practices are not adequate to maintain airborne concentrations below the established exposure guidelines, additional ventilation or exhaust systems may be required. Where explosive mixtures may be present, electrical systems safe for such locations must be used.

PERSONAL PROTECTIVE EQUIPMENT

EYES AND FACE: Wear safety glasses with side shields or goggles when handling this material.

SKIN: To prevent any contact, wear impervious protective clothing such as nitrile or butyl rubber gloves, apron, boots or whole bodysuit, as appropriate.

RESPIRATORY: Use NIOSH/MSHA approved respirators when vapors or mist concentrations exceed permissible exposure limits.

PROTECTIVE CLOTHING: Chemical resistant boots, apron, etc. as necessary to prevent contamination of clothing and skin contact.

WORK HYGIENIC PRACTICES: Good personal hygiene practices should always be followed.

9. PHYSICAL AND CHEMICAL PROPERTIES

Chemical Name	Flash Point (°C)	Specific Gravity
Stoddard solvent	43	0.79

PHYSICAL STATE: Liquid

ODOR: Mild Hydrocarbon Odor

APPEARANCE: Clear

COLOR: Colorless

pH: Not Applicable

PERCENT VOLATILE: 100

FLASHPOINT AND METHOD: ~ (110°F) TAG CC

FLAMMABLE LIMITS: ~1 to ~7

VAPOR PRESSURE: 2.9 mmHg

VAPOR DENSITY: 4.8 (Air=1)

BOILING POINT: (310°F) to (355°F)

FREEZING POINT: Not Determined

SAFETY DATA SHEET



Date Issued : 07/18/2000
MSDS No : 210090
Date-Revised : 12/19/2017
Revision No : 9

Rule 66 Quick Dry

MELTING POINT: Not Determined
SOLUBILITY IN WATER: Negligible
EVAPORATION RATE: 0.21 (n-Butyl Acetate=1)
DENSITY: 6.45 at (60°F)
SPECIFIC GRAVITY: 0.78 (water=1) at (60°F)

10. STABILITY AND REACTIVITY

REACTIVITY: No
HAZARDOUS POLYMERIZATION: Will not occur
STABILITY: Stable
CONDITIONS TO AVOID: Exposure to excessive heat, open flames and sparks. Avoid conditions that favor the formation of excessive mists and/or fumes.
HAZARDOUS DECOMPOSITION PRODUCTS: Oxides of Carbon when burned.
INCOMPATIBLE MATERIALS: Strong oxidizing agents.

11. TOXICOLOGICAL INFORMATION

GENERAL COMMENTS:

All components listed have been shown to contain less than 3% DMSO extractables as measured by IP346.

COMMENTS: No definitive information available on carcinogenicity, target organs or chronic toxicity.

12. ECOLOGICAL INFORMATION

ENVIRONMENTAL DATA: KEEP OUT OF SURFACE WATERS, SEWERS, AND WATERWAYS ENTERING OR LEADING TO SURFACE WATERS. NOTIFY AUTHORITIES IF ANY EXPOSURE TO THE GENERAL PUBLIC OR ENVIRONMENT OCCURS OR IS LIKELY TO OCCUR.

13. DISPOSAL CONSIDERATIONS

DISPOSAL METHOD: Conditions of use may cause this material to become a hazardous waste as defined by state or federal law. Use approved treatment, transporters and disposal sites.
FOR LARGE SPILLS: Extinguish possible sources of ignition. Evacuate all unprotected personnel and ventilate area. Only personnel equipped with proper respiratory, skin/eye protection should enter spill area. Dike area to contain spill and clean up by absorbing on an inert absorbent or other means. Don't flush into sewers or natural waterways.
PRODUCT DISPOSAL: Dispose of at a supervised incineration facility or an appropriate waste disposal facility according to current applicable laws and regulations and product characteristics at time of disposal.
EMPTY CONTAINER: Keep containers closed when not in use. Do not reuse empty containers.

14. TRANSPORT INFORMATION

DOT (DEPARTMENT OF TRANSPORTATION)

PROPER SHIPPING NAME: Petroleum Distillates, N.O.S.
PRIMARY HAZARD CLASS/DIVISION: 3

SAFETY DATA SHEET



Date Issued : 07/18/2000
 MSDS No : 210090
 Date-Revised : 12/19/2017
 Revision No : 9

Rule 66 Quick Dry

UN/NA NUMBER: 1268

PACKING GROUP: II

LABEL: Class 3, Flammable Liquid

15. REGULATORY INFORMATION

UNITED STATES

SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT)

311/312 HAZARD CATEGORIES: Fire Hazard, Acute (Immediate) Health Hazard.

313 REPORTABLE INGREDIENTS: None known to be present at 1% or more by weight (0.1% for Carcinogens)

TSCA (TOXIC SUBSTANCE CONTROL ACT)

Chemical Name	CAS
Stoddard solvent	8052-41-3

TSCA REGULATORY: This material or its components are listed in the TSCA inventory.

CALIFORNIA PROPOSITION 65: This material contains the following chemicals which are known to the State of California to cause cancer, birth defects or other reproductive harm, and are subject to the requirements of California Proposition 65 (CA Health & Safety Code Section 25249.5): Component Effect Benzene - Cancer Toluene - Developmental Toxicant

16. OTHER INFORMATION


Date-Revised: 12/19/2017

REVISION SUMMARY: This MSDS replaces the 04/23/2015 MSDS.

HMIS RATING

HEALTH	-	1
FLAMMABILITY		2
PHYSICAL HAZARD		0
PERSONAL PROTECTION		C

NFPA CODES



ADDITIONAL MSDS INFORMATION: Caution! Combustible. Treat as an OSHA Class II Combustible Liquid. Acute health effects include possible skin irritation via contact by liquid, irritation of nose, throat and respiratory tract from inhaling vapors and a serious aspiration hazard if swallowed. Higher concentrations of vapors may result in CNS depression, I.E., headaches, dizziness and nausea. Chronic health effects include defatting and drying of the skin which may result in skin irritation and dermatitis. Additionally, lab animal studies of exposure to vapors via inhalation showed evidence of kidney damage. Avoid breathing vapors and contact with eyes or skin.

MANUFACTURER DISCLAIMER: The information in this SDS was obtained from sources which we believe are reliable. However, the above information is provided without warranty, expressed or implied, regarding its correctness. The conditions or methods of handling, storage, use and disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product.