



## 15W40 Motor Oil

**ATI X 15W40 Heavy Duty Diesel Motor Oil** is specifically engineered to meet the latest requirements for EGR / EGP engines.

### APPLICATIONS

Meets or exceeds API CK-4/SN, and is backwards compatible with CJ-4, CI-4 PLUS, CI-4 and CH-4. Meets meet MACK EOS-4.5, EO-0 Premium Plus, EO-N, Volvo VDS-4.5, VDS-4, VDS-3, Caterpillar ECF-3, ECF-2, CumminsCES20086, CES 20081, CES20087, DD DFS, 93K222, DFS 93K218, DFS 93K233, Daimler MB228.31, MTU Category 2.1 and Renault RLD-4, RLD-3.

### FEATURES/BENEFITS

**ATI X 15W40's** robust formulation includes the highest quality Group II+ base oils with exceptional purity and lubricating properties that heavy-duty applications demand. State-of-the-art performance additives include viscosity index improvers, detergents, dispersants and anti-wear agents for maximum protection against breakdown and engine wear. ATI X 15W40 provides unmatched varnish, sludge and carbon deposit control in addition to low valve train, ring and linear wear. Other benefits include extra protection against bearing and bushing corrosion, boosted oxidation control to minimize oil thickening and excellent high temperature stability.

### TYPICAL PROPERTIES

### 15W-40

API Service	CK-4
cSt @ 40°C	113.9
cSt @ 100°C	15.6
Viscosity Index	145
Specific Gravity @ 60°F (15.6°C)	0.869
Sulphated Ash, wt%	1.0
Pour Point, °C	-33
Flash Point °C	226
CCS Viscosity, cP	5500 (-20 °C)
Color (ASTM)	L 4.0
TBN	10.0



Distributed by Shrader Tire & Oil Co.